

SPECIFICATIONS - STANDARD TRACKING SYSTEM WITH COMBINATION DOLLY

Remote Heads

| | |
|-------------------------------------|---|
| Camera (max 2) | Any tri-ax camera, Panasonic AWE800 |
| Lens (max 2) | Canon, Sony, Fujinon |
| Remote Head | Any combination of Hotshot, Minishot, Type IIR Head |
| Lens height (from floor or support) | min 350mm/max 1100mm |

Track Sizes

| | |
|---|---|
| Track gauge | 300 mm |
| Track length (2m sections) | Up to 60m |
| Width for safe clearance of track | 650mm |
| Width for safe clearance of camera and head | 750mm |
| Height for clearance | Hotshot = 1200mm, Minishot = 450mm, Type 2R Digital = 600mm |

Track Speeds

| | |
|---------------------------------------|--------------|
| Max Speed - 3 phase power | 6m/sec |
| Max Acceleration - 3 phase power | 4.5m/sec*sec |
| Max Speed - Single phase power | 3.5m/sec |
| Max Acceleration - Single phase power | 3m/sec*sec |

Track Control

| | |
|-----------------|--|
| Motion control | Fully programmed end stops/Accel/Decel/Safety cut-outs |
| Operator inputs | Proportional Joystick/Proportional Foot pedals/Button Console/Directional Footswitches |

Special Requirements

| | |
|--------------------|----------------------------|
| Operating Position | In operators line of sight |
|--------------------|----------------------------|

Track Power & Cabling

| | |
|---|---|
| Power Supply | 32 amp, 3 phase or 13 -16 amp, single phase |
| Max distance to operating position for cables | 100m |

Shipping Weights & Sizes - (20m System)

| | |
|---|--|
| | Sizes in mm : Length x Width x Height - Weight in kg |
| Gross Weight | 920kg |
| Motor Units - wheeled flight case | L =1000 x W=550 x H=1200 - 65kg |
| Track - 10 sections (1 wheeled pallet) | L =2000 x W=760 x H=1350 - 475kg |
| Dolly/Single Phase Drive/Cables/ Control Console/Operators Kit/Spares - wheeled flight case | L =1400 x W=650 x H=1100 - 250kg |
| Remote Head - Hotshot | L =1000 x W=250 x H=600 - 35kg |
| Remote Head - Hotshot Control | L =1000 x W=250 x H=600 - 35kg |
| Remote Head - Minishot | L =500 x W=400 x H=400 - 25kg |
| Remote Head - Type 2R Digital | L =1000 x W=250 x H=600 - 35kg |

Shipping Weights & Sizes - (50m System)

| | |
|--|--|
| | Sizes in mm : Length x Width x Height - Weight in kg |
| Gross Weight | 1835kg |
| Motor Units - wheeled flight case | L =1000 x W=550 x H=1200 - 65kg |
| Track - 26 sections (3 wheeled pallets) | L =2000 x W=760 x H=1350 - 475kg |
| Dolly/Single Phase Drive Cables/Control Console/Operators Kit/Spares - wheeled flight case | L =1400 x W=650 x H=1100 - 250kg |
| Camera (max 2) | L =1000 x W=250 x H=600 - 35kg |
| Remote head - Hotshot Control | L =1000 x W=250 x H=600 - 35kg |
| Remote head - Minishot | L =500 x W=400 x H=400 - 25kg |
| Remote Head - Type 2R Digital | L =1000 x W=250 x H=600 - 35kg |

This information is for guidance only and may differ subject to requirements

300mm GAUGE TRACK WITH TWO REMOTE HEADS DOLLY

