

SPECIFICATIONS - STANDARD TRACKING SYSTEM WITH HOTSHOT/HANDHELD CAMERA

Remote Head	
Camera	Any tri-ax camera, Panasonic AWE800
Lens	Canon, Sony, Fujinon
Remote Head	Hotshot with Joystick control
Lens height (from floor or support)	Min 650mm/Max1100mm
Track Sizes	
Track gauge	300mm
Track length (2m sections)	Up to 60m
Width for safe clearance of track	650mm
Width for safe clearance of camera and head	750mm
Height for clearance	600mm
Track Speeds	
Max Speed - 3 phase power	6m/sec
Max Acceleration - 3 phase power	4.5m/sec*sec
Max Speed - Single phase power	3.5m/sec
Max Acceleration - Single phase power	3m/sec*sec
Track Control	
Motion control	Fully programmed Endstops/Accel/Decel/Safety cut-outs
Operator inputs	Proportional Joystick/Proportional Footpedals/Button Console/Directional Footswitches
Special Requirements	
Operating Position	In operators line of sight
Track Power & Cabling	
Power Supply	32 amp, 3 phase or 13 -16 amp, single phase
Max distance to operating position for cables	100m
Shipping Weights & Sizes - (20m System)	
Gross Weight	920kg
Motor Units - wheeled flight case	L =1000 x W=550 x H=1200 - 65kg
Track - 10 sections (1 wheeled pallet)	L =2000 x W=760 x H=1350 - 475kg
Dolly/Single Phase Drive/Cables/Control Console/Operators Kit /Spares - wheeled flight case	L =1400 x W=650 x H=1100 - 250kg
Remote head - Hotshot Head	L =1000 x W=250 x H=600 - 35kg
Remote head - Hotshot Control	L =1000 x W=250 x H=600 - 35 kg
Shipping Weights & Sizes - (50m System)	
Gross Weight	1835kg
Motor Units - wheeled flight case	L =1000 x W=550 x H=1200 - 65kg
Track - 26 sections (3 wheeled pallets)	L =2000 x W=760 x H=1350 - 475kg
Dolly/Single Phase Drive/Cables/Control Console/Operators Kit / Spares - wheeled flight case	L =1400 x W=650 x H=1100 - 250kg
Remote head - Hotshot Head	L =1000 x W=250 x H=600 -35kg
Remote head - Hotshot Control	L =1000 x W=250 x H=600 - 35kg
This information is for guidance only and may differ subject to requirements	

300mm GAUGE TRACK WITH HOTSHOT AND STANDARD DOLLY

